

GENERAL RTD

Approvals:



<p>GRA</p>	<p>GRB</p>
<p>GRC</p>	<p>GRD</p>
<p>GRE</p>	<p>GRF</p>
<p>GRG</p> <p>1/8" NPT <input type="checkbox"/> Standard <input type="checkbox"/> Option</p>	<p>GRH</p>
<p>GRI</p>	<p>GRJ</p> <p>1/8" NPT <input type="checkbox"/> Standard <input type="checkbox"/> Option</p> <p>Cable</p> <p>Head</p>
<p>GRK (Heat Trace Type)</p> <p>Surface Pad</p> <p>Weld</p> <p>O.D.</p>	

Ordering Information

Model	GRA	GRB	GRC	GRD	GRE	GRF	GRG	GRH	GRI	GRJ	GRK	
<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">↓</div> <div style="text-align: center;">↓</div> <div style="text-align: center;">↓</div> <div style="text-align: center;">↓</div> <div style="text-align: center;">↓</div> <div style="text-align: center;">↓</div> <div style="text-align: center;">↓</div> <div style="text-align: center;">↓</div> </div>	Code	Sensor Dimensions "O.D" mm										
		(1) 1.6 (2) 3.2 (3) 4.8 (4) 6.0 (5) 8.0 (6) 9.0 (7) 12.75 (8) 1.0 (9) 1.2										
		(10) 2.3 (11) 2.7 (12) 3.0 (13) 3.175 (14) 3.8 (15) 4.0 (16) 4.5 (17) 4.72										
		(18) 5.0 (19) 6.35 (20) 6.4 (21) 10.0 (22) 12.0 (23) 12.7 (24) 13.8										
		(25) 15.0 (26) 16.0 (27) 18.0 (28) 19.0 (29) 20.0 (30) 21.34 (31) 21.7										
	Code	Sheath Material										
	A	SS316/SS316L			O	Option						
	Code	Element Type										
	1	PT100Ω										
	Code	Element No.										
	S	Single				D	Double					
	Code	Sensor Class										
		(1) Class A (2) Class B										
	Code	Sensor Insertion Length "L"										
		Please directly fill in the requesting length (mm).										
Code	Lead Wire Length "E"											
	Please directly fill in the requestion length (mm).											
												Complete Ordering Code