FLOW SIGHT GLASS GAUGE

Self Clearing Available

NAM is used for mounting in pipes for fluids. The instruments are equipped with female threads at inlet and outlet and can be supplied with either brass or stainless steel fittings.

Technical Data

Self Clearing Function Available

Material: Body- SS316L; Tube Housing- Glass; O-Ring- Viton, NBR available Rotor-POM (Orange), PP+10% glass fiber (Yellow), PPS+40% glass fiber (Dark Brown), PVDF (Red or White) available; Rotor Guide-SS316; Thread Connection-SS316

Viscosity: 1~150 mm²/s

Indication Range: Minimum 0,4~4 L/Min; Maximum 8~100 L/Min for water

Max. Pressure: SS316L body: 16 bar @20°C

Max. Temperature: SS316L body: -5°C~+150°C; Rotors: Please refer to the Optional for Rotors


Connetion Size: 1/4", 3/8", 1/2", 3/4", 1", 11/4", 11/2" female PF or NPT available



Approvals:



Dimensions



Dimension Data & Range Table:

unit=mm

SIZE	ı		SPANNER SIZE (AF)	FLOW RANGE (WATER)				
	NPT	PF	NPT/PF	(WATER)				
1/4"	71	71	36	0.4~4 L/Min				
3/8"	71	71	36	0.6~8 L/Min				
1/2"	86 86		46	1~12 L/Min				
3/4"	94	94	46	1~25 L/Min				
1"	104	104 46		1.6~40 L/Min				
11/4"	120	120	65	8~80 L/Min				
1½"	130	130	65	8~100 L/Min				

Flow Direction



Optional for Rotors





PP+10% Glass Fiber Color: Yellow Temp. Limit: 60°C



PPS+40% Glass Fiber Color: Dark Brown Temp. Limit: 200°C



PVDF Color: Red or White Temp. Limit: 100°C

The temperature limit above-mentioned is only for the reference to the rotors. Please also considering the max. temperature of body in the operating.

Ordering Information																	
NAN	/	Code	Туре	ре						Rotor Material (Color)							
		1	With R	Rotor 2 Without Rotor						POM (Orange)							
			Code	Body /	/laterial	2	2	PP+10% Glass Fiber (Yellow)									
			1	SS316	L / Glas	SS		3	3	PPS+40% Glass Fiber (Dark Brown)							
			Code Coni			ction Siz	ze	4	ŀ	PVDF (Red)		ed)	5	PVDF (White)	N	Without Rotor	
			(1) 1/4			4" (2) 3	/8" (3) 1/2"				e S	Self Clo	Clearing Vith (2) Without				
				(4) 3/4			" (5) 1" (6) 1¼" (7) 1½"				(1) Witl					
				Code 1			ction Rating					Code	C € 1128 Mark Request				
							emale					1	With	ı label sticker			
			2			PF Fer	male					2	With S.S nameplate				
						Code	O-Ring Material					3	Star	np			
						V	Viton					4	With	nout			
						N	NBR										
•		\	*	*	▼	•		1	7	*		▼					
NAN	/						+						Cor	nplete Ordering	Code		